Grip Caps

GPN 212

PÖPPELMANN® KAPSTO®

Application

The GPN 212 grip caps are particularly suitable for protecting pipes and ball sockets. The ergonomically shaped grip tab facilitates easy handling during fitting and removal. The flexible material allows the use of different counterpart geometries and is heat-resistant up to 150° C for short periods.

All information about the recycling blend can be found in at www.poeppelmann.com/en/kapsto/Responsibility.html



Article	D min	D max	G	M	PCR-TPE yellow Recycling blend	TPE yellow Virgin material
GPN 212 FM 76	8	8,8	7,8	23,3	21200760085	21200760000
GPN 212 FM 77	8	9	10,1	25,4	21200770085	21200770000
GPN 212 FM 88*	9,4	10,1	11,1	26,8	21200880085	21200880000
GPN 212 FM 102	10,3	11,2	8,7	24,2	21201020085	21201020000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 4 'Materials and application'.

* This size is supplied with internal clamping surfaces.

Customer Information pursuant to Art. 16 of the PPWR (EU Regulation 2025/40): To the best of our current knowledge and based on information from our raw material suppliers, the products we supply do not contain the heavy metals listed in Article 5, paragraph 4 of the PPWR (lead, cadmium, mercury, and hexavalent chromium) in a total concentration exceeding 100 mg/kg. Pöppelmann neither intentionally adds these regulated substances as components nor are they expected to be present in impermissible concentrations as impurities resulting from the manufacturing process.

Furthermore, according to information from our suppliers, our products do not contain any substances of very high concern (SVHCs as defined in the current REACH Candidate List) in a concentration exceeding 0.1 percent by mass. Pöppelmann does not intentionally add these substances during the manufacturing process. Any presence below this reportable threshold is attributable to unavoidable, raw material-related impurities or technical specifications set by raw material suppliers, which, for us as a processor, represents the technically unavoidable minimum within the context of quality and raw material properties.

Your added values:

Saves time.
With ergonomically designed removal tab for easy handling.

Higher temperature resistance.
Heat resistant to 150 °C.

More versatile.
Suitable for different diameters due to flexible material. Free from plasticizers with SVHC** relevance.

Better.
Particularly suitable for ball linings.

Seals better.
Protection against foreign objects>1 mm

Link to GPN 212