





## Application

The GPN 212 grip caps are particularly suitable for protecting pipes and ball sockets. The ergonomically shaped grip tab facilitates easy handling during fitting and removal. The flexible material allows the use of different counterpart geometries and is heat-resistant up to 150° C for short periods.

All information about the recycling blend can be found in "Sustainability at Pöppelmann" (see chapter 2) or at [www.poeppelmann.com/en/kapsto/Responsibility.html](http://www.poeppelmann.com/en/kapsto/Responsibility.html)



PCR-TPE  
yellow



TPE  
yellow

Article	D min	D max	G	M	Recycling blend	Virgin material
GPN 212 FM 76	8	8,8	7,8	23,3	21200760085	21200760000
GPN 212 FM 77	8	9	10,1	25,4	21200770085	21200770000
GPN 212 FM 88*	9,4	10,1	11,1	26,8	21200880085	21200880000
GPN 212 FM 102	10,3	11,2	8,7	24,2	21201020085	21201020000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 3 'Materials and application'.

\* This size is supplied with internal clamping surfaces.

The article consists of a mixture of PCR (Post Consumer Recyclate) and virgin TPE (Thermoplastic Elastomers). Colour deviations and black dots cannot be completely avoided during production and are permissible for these items. We recommend carrying out functional tests before series production.

## Your added values:



### More resource-saving.

The plastic used contains PCR and conserves resources.



### Saves time.

With ergonomically designed removal tab for easy handling.



### Higher temperature resistance.

Heat resistant to 150 °C.



### More versatile.

Suitable for different diameters due to flexible material. Free from plasticizers with SVHC\*\* relevance.



### Better.

Particularly suitable for ball linings.