

Grip Plugs GPN 330






www.poeppelmann.com/en/gpn330

Application

The GPN 330 grip plugs are suitable for protecting bore holes and internal threads as well as for special fittings with union nuts. The ribs engage in the threads and position the union nut at the end of the pipe. The tab is designed to be easy to handle, install and remove. Flexible ribs accommodate larger tolerances.

All information about 100% PCR and the recycling blend can be found in "Sustainability at Pöppelmann" (see chapter 2) or at www.poeppelmann.com/en/kapsto/Responsibility.html



PCR-PE
blue



PCR-PE / PE-LD
yellow



PE-LD
yellow

Article	A	B	C	D	G	H	M	100% PCR	Recycling blend	Virgin material
GPN 330 L 10	16	6,4	10,5	4,4	5,5	4,1	26,5	3300010RB61	33000100073	33000100000
GPN 330 L 12	14,3	6,4	12,3	4,4	5,5	4,1	26,5	3300012RB61	33000120073	33000120000
GPN 330 L 14	16,3	8,4	14,3	6,4	5,5	4,1	26,5	3300014RB61	33000140073	33000140000
GPN 330 L 16	18,3	10,4	16,3	8,4	5,5	4,1	26,5	3300016RB61	33000160073	33000160000
GPN 330 L 18	21	10,4	18,5	8,4	5,5	4,1	26,5	3300018RB61	33000180073	33000180000
GPN 330 L 19	21	13,6	19,7	11,6	8,3	6,1	29,3	3300019RB61	33000190073	33000190000
GPN 330 L 20	22,5	13,6	20,7	11,6	8,3	6,1	29,3	3300020RB61	33000200073	33000200000
GPN 330 L 22	25	16,4	22,9	14,4	8,3	7,6	29,3	3300022RB61	33000220073	33000220000
GPN 330 L 24	27	16,4	24,9	14,4	8,3	7,6	29,3	3300024RB61	33000240073	33000240000
GPN 330 L 27	30	19,6	27,9	17,6	8,3	8,1	29,3	3300027RB61	33000270073	33000270000
GPN 330 L 28	31	19,6	28,8	17,6	8,3	7,9	29,3	3300028RB61	33000280073	33000280000
GPN 330 L 39	46	26,2	39,5	24,2	11,4	11	32,4			33000390000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 3 'Materials and application'.

The articles in the 100% PCR column consist of 98% PCR-PE and 2% colour based on a PIR carrier. The plastic used consists of 100% PCR.

The articles in the recycled mixture column consist of a blend of PCR and virgin material. Colour deviations and black dots cannot be completely avoided during production and are permissible for these items. We recommend carrying out functional tests before series production.

Application guide for internal use

Article	Female thread	Fine thread	Pipe thread
GPN 330 L 12	M 12	M 10 x 1 M 12 x 1	1/4 1/8
GPN 330 L 14	M 14	M 14 x 1	1/4
GPN 330 L 16	M 16	M 16 x 1	3/8
GPN 330 L 18	M 18	M 18 x 1 M 19 x 1,5	3/8
GPN 330 L 19	M 20	M 18 x 1 M 20 x 1	1/2
GPN 330 L 20		M 20 x 1	1/2
GPN 330 L 22	M 24	M 22 x 1 M 22 x 1,5	5/8
GPN 330 L 24	M 24	M 24 x 1 M 25 x 1	5/8
GPN 330 L 27	M 27	M 26 x 1 M 27 x 1	3/4
GPN 330 L 28	M 30	M 27 x 1 M 28 x 1	7/8
GPN 330 L 39	M 39	M 34 x 1 M 35 x 1 M 36 x 1 M 37 x 1	



PÖPPELMANN®
KAPSTO®

Grip Plugs GPN 330



www.poeppelmann.com/en/gpn330

This application table is a guide. We will be happy to send you free test samples. For openings and bores without threads, please select according to functional dimensions B and C.

Your added values:



More resource-saving.

This standard series is available from PCR, saves CO₂e emissions and conserves resources.



Saves time.

Practical tab for easy handling.



More versatile.

Flexible shaft ribs for accommodating large tolerances.



Better.

Suitable for bores and inner threads. Can also be used for pipelines with union nut. The lamellae engage into the thread and position the union nut at the end of the line.



PÖPPELMANN®
KAPSTO®