



# Tapered Plugs GPN 605



www.poeppelmann.com/en/gpn605

## Application

The GPN 605 tapered plugs offer protection for openings, bore holes and internal threads against dirt and damage. The solid design is suitable for increased loads. The conical shape is ideal for accommodating tolerances. The material is extremely heat-resistant up to 250° C for short periods.



SI  
natural

| Article        | B   | C    | H    | Virgin material |
|----------------|-----|------|------|-----------------|
| GPN 605 / 0832 | 0,8 | 3,2  | 16   | 60508320000     |
| GPN 605 / 1632 | 1,6 | 3,2  | 16   | 60516320000     |
| GPN 605 / 1648 | 1,6 | 4,8  | 16   | 60516480000     |
| GPN 605 / 3263 | 3,2 | 6,3  | 19   | 60532630000     |
| GPN 605 / 4887 | 4,8 | 8,7  | 16   | 60548870000     |
| GPN 605 / 6395 | 6,3 | 9,5  | 19   | 60563950000     |
| GPN 605 / 6312 | 6,3 | 9,5  | 13   | 60563120000     |
| GPN 605 / 8011 | 8   | 11   | 27   | 60580110000     |
| GPN 605 / 9012 | 9   | 12   | 18   | 60590120000     |
| GPN 605 / 1015 | 10  | 15   | 25   | 60510150000     |
| GPN 605 / 1316 | 13  | 16   | 19   | 60513160000     |
| GPN 605 / 1317 | 13  | 17   | 25   | 60513170000     |
| GPN 605 / 1419 | 14  | 19   | 25   | 60514190000     |
| GPN 605 / 1620 | 16  | 20   | 25   | 60516200000     |
| GPN 605 / 1824 | 18  | 24   | 25   | 60518240000     |
| GPN 605 / 2026 | 20  | 26   | 25   | 60520260000     |
| GPN 605 / 2327 | 23  | 27   | 25   | 60523270000     |
| GPN 605 / 2428 | 24  | 28   | 25   | 60524280000     |
| GPN 605 / 2632 | 26  | 32   | 25   | 60526320000     |
| GPN 605 / 2734 | 27  | 34   | 25   | 60527340000     |
| GPN 605 / 3037 | 30  | 37   | 25   | 60530370000     |
| GPN 605 / 3139 | 31  | 39   | 25   | 60531390000     |
| GPN 605 / 3341 | 33  | 41   | 25   | 60533410000     |
| GPN 605 / 3643 | 36  | 43   | 25   | 60536430000     |
| GPN 605 / 3745 | 37  | 45   | 25   | 60537450000     |
| GPN 605 / 3846 | 38  | 46   | 25   | 60538460000     |
| GPN 605 / 4250 | 42  | 50   | 25   | 60542500000     |
| GPN 605 / 4553 | 45  | 53   | 25   | 60545530000     |
| GPN 605 / 4856 | 48  | 56   | 25   | 60548560000     |
| GPN 605 / 5060 | 50  | 60   | 45   | 60550600000     |
| GPN 605 / 5464 | 54  | 63,5 | 25,5 | 60554640000     |
| GPN 605 / 6275 | 62  | 75   | 35   | 60562750000     |
| GPN 605 / 1013 | 10  | 13   | 18   | 60510130000     |
| GPN 605 / 1114 | 11  | 14   | 18   | 60511140000     |

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 3 'Materials and application'.

Clear burrs as well as partial foreign particles are permissible with these articles. We recommend that functional tests be carried out before series production.

## Tapered Plugs GPN 605



[www.poeppelmann.com/en/gpn605](http://www.poeppelmann.com/en/gpn605)

### Your added values:



**Higher temperature resistance.**

Extremely heat resistant up to 250 °C



**More robust.**

Solid design for higher demands.



**More versatile.**

The tapered design is ideal for accommodating large tolerances.



**Better.**

Suitable for closing off apertures, bore holes and internal threads.