



Pull Plugs GPN 606



www.poeppelmann.com/en/gpn606

Application

The GPN 606 pull plugs offer protection for through holes with and without thread against dirt and damage. The pull tab enables easy installation and removal. The solid design is suitable for increased loads. The material is extremely heat-resistant up to 250° C for short periods.



Article	B	C	H	M	Virgin material
GPN 606 / 0023	1,3	2,3	15,9	32,3	60600230000
GPN 606 / 0033	2,2	3,3	15,9	32,3	60600330000
GPN 606 / 0041	2,1	4,1	15,9	31,5	60600410000
GPN 606 / 0050	2,8	5	15,9	35,5	60600500000
GPN 606 / 0055	3,3	5,5	25,4	51,4	60600550000
GPN 606 / 0070	3,2	7	23,8	47,6	60600700000
GPN 606 / 0080	3,7	7,9	25,4	54,4	60600800000
GPN 606 / 0085	3,9	8,5	25,4	53,2	60600850000
GPN 606 / 0095	4	9,5	25,4	51,2	60600950000
GPN 606 / 0104	4,3	10,4	25,6	53,8	60601040000
GPN 606 / 0112	6,6	11,2	25,4	53	60601120000
GPN 606 / 0126	6,4	12,6	25,4	53,8	60601260000
GPN 606 / 0156	6,4	15,4	25,4	56	60601560000
GPN 606 / 0163	9,5	16,3	25,4	54,5	60601630000
GPN 606 / 0178	9,5	17,8	31,8	56,4	60601780000
GPN 606 / 0196	9,5	19,6	25,4	56,3	60601960000
GPN 606 / 0205	8	20,6	25,4	57,5	60602050000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 3 'Materials and application'.

Application guide for internal use

Article	Female thread	Fine thread	Pipe thread
GPN 606 / 0033	M 4		
GPN 606 / 0041	M 5		
GPN 606 / 0050	M 5		
GPN 606 / 0055	M 6		
GPN 606 / 0070	M 8		G 1/6
GPN 606 / 0080	M 9		
GPN 606 / 0085	M 10		
GPN 606 / 0095	M 11		G 1/8
GPN 606 / 0104	M 12	M 12 x 1,5	
GPN 606 / 0112	M 12	M 12 x 1,5	
GPN 606 / 0126	M 14	M 14 x 1,5	G 1/4
GPN 606 / 0156		M 16 x 1,5 M 17 x 1,5	
GPN 606 / 0163	M 18	M 16 x 1 M 17 x 1	M 18 x 2 G 3/8
GPN 606 / 0178	M 20	M 18 x 1	M 19 x 1,5
GPN 606 / 0196	M 22	M 20 x 1	M 20 x 1,5 G 1/2
GPN 606 / 0205	M 22	M 22 x 1,5	

This application table is a guide. We will be happy to send you free test samples. For openings and bores without threads, please select according to functional dimensions B and C.

Clear burrs as well as partial foreign particles are permissible with these articles. We recommend that functional tests be carried out before series production.

Pull Plugs GPN 606



www.poeppelmann.com/en/gpn606

Your added values:



Saves time.

With pull tab Ø B for easy fitting and removal.



Higher temperature resistance.

Extremely heat resistant up to 250 °C



More robust.

Solid design for higher demands.



Better.

Suitable for through holes with or without thread. Ø C closes off, Ø B is used as pull tab..