



Flange Caps GPN 680



www.poeppelmann.com/en/gpn680

Application

The GPN 680 flange caps are suitable for the protection of flanges as per DIN EN 12351 and are particularly ideal for protecting fittings with solid linings or a conical bore hole from damage and dirt. The hook-snaps ensure a firm fit on the application.



PE-LLD
yellow

Article	Nominal width mm	Nominal pressure	D	E	G	Virgin material
GPN 680 DN 10	10	10; 16; 25; 40	90	81	17	68000100000
GPN 680 DN 15	15	10; 16; 25; 40	95	86	17	68000150000
GPN 680 DN 20	20	10; 16; 25; 40	105	96	19	68000200000
GPN 680 DN 25	25	10; 16; 25; 40	115	106	19	68000250000
GPN 680 DN 32	32	10; 16; 25; 40	140	131	19	68000320000
GPN 680 DN 40	40	10; 16; 25; 40	150	141	19	68000400000
GPN 680 DN 50	50	10; 16; 25; 40	165	156	21	68000500000
GPN 680 DN 65	65	10; 16; 25; 40	185	176	22	68000650000
GPN 680 DN 80	80	10; 16; 25; 40	200	191	24	68000800000
GPN 680 DN 100	100	10; 16	220	211	24	68001000000
GPN 680 DN 125	125	10; 16	250	241	25	68001250000
GPN 680 DN 150	150	10; 16	285	276	25	68001500000
GPN 680 DN 200	200	10; 16	340	331	27	68002000000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 3 'Materials and application'.

Your added values:



Better fit.

Protection for flanges in accordance with DIN EN 12351.



Better.

Particularly suitable for fittings with solid lining or tapered bore holes. With hook-snaps for firm fit.