






Application

The GPN 950 protective covers can be used universally as a cap or a plug and can be used for bore holes, internal and external threads and pipe ends. They have a knurled collar for easier assembly and disassembly.

All information about 100% PCR and the recycling blend can be found in "Sustainability at Pöppelmann" (see chapter 2) or at www.poeppelmann.com/en/kapsto/Responsibility.html



www.blauer-engel.de/uz30a



PCR-PE
blue

PCR-PE / PE-LD
yellow

PE-LD
natural

Article	A	C	D	G	H	100% PCR	Recycling blend	Virgin material
GPN 950 / 0054	10	5,4	3,9	7,3	6	9500054RB61	95000541073	95000540000
GPN 950 / 0067	10,5	6,7	5,2	7,8	7	9500067RB61	95000671073	95000670000
GPN 950 / 0072	14	7,2	5,7	7,2	6,5	9500072RB61	95000721073	95000720000
GPN 950 / 0092	16	9,6	7,7	7,2	6,5	9500092RB61	95000921073	95000920000
GPN 950 / 0105	20	10,5	8,4	6,2	5	9500105RB61	95001051073	95001050000
GPN 950 / 0106	18	10,6	9	9,2	8,5	9500106RB61	95001061073	95001060000
GPN 950 / 0126	20	12,6	11	9,2	8	9500126RB61	95001261073	95001260000
GPN 950 / 0131	22	13,1	11,5	9,2	8	9500131RB61	95001311073	95001310000
GPN 950 / 0147	22	14,7	13,1	11,2	10	9500147RB61	95001471073	95001470000
GPN 950 / 0157	20	15,7	13,5	8,9	8	9500157RB61	95001571073	95001570000
GPN 950 / 0168	24	16,8	15,5	9,2	8,5	9500168RB61	95001681073	95001680000
GPN 950 / 0180	24	18	16	8	7,2	9500180RB61	95001801073	95001800000
GPN 950 / 0188	28	18,8	17,5	11,2	10	9500188RB61	95001881073	95001880000
GPN 950 / 0193	28	19,3	17,7	11,2	10	9500193RB61	95001931073	95001930000
GPN 950 / 0208	30	20,8	19,5	11,2	10	9500208RB61	95002081073	95002080000
GPN 950 / 0229	31,8	22,9	21,7	11,4	10	9500229RB61	95002291073	95002290000
GPN 950 / 0250	33,5	25,1	23,6	11,3	10	9500250RB61	95002501073	95002500000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 3 'Materials and application'.

The articles in the 100% PCR column consist of 98% PCR-PE and 2% colour based on a PIR carrier. The plastic used consists of 100% PCR.

The articles in the recycled mixture column consist of a blend of PCR and virgin material. Colour deviations and black dots cannot be completely avoided during production and are permissible for these items. We recommend carrying out functional tests before series production.

Your added values:



More resource-saving.

This standard series is available from PCR, saves CO₂e emissions and conserves resources.



More versatile.

Can be used as cap or plug.



Cleaner.

Production in accordance with VDA Band 19 and ISO 16232 in our cleanroom on request.



Better.

With knurled collar. Suitable for bore holes, internal and external threads, or pipe ends.



PÖPPELMANN®
KAPSTO®