



Protective Caps

GPN 200 Type B

Application

The protective caps GPN 200 Type B are designed for male end connectors pursuant to DIN EN 837-1 and DIN EN 837-3. The easy-to-grip, knurled outer wall enables easy removal.

All information about 100% PCR and the recycling blend can be found at www.poeppelmann.com/en/kapsto/Responsibility.html



Article	External thread	D	G	O	100% PCR	Recycling blend	Virgin material
GPN 200 / 1040	M 12 x 1.5	12	12	16	2001040RB61	20010401073	20010400000
GPN 200 / 0790	M 20 x 1.5	20	20	26	2000790RB61	20007901073	20007900000
GPN 200 / 1041	G 1/4	13	12	16	2001041RB61	20010411073	20010410000
GPN 200 / 0791	G 1/2	21	20	26	2000791RB61	20007911073	20007910000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 4 'Materials and application'.

Customer Information pursuant to Art. 16 of the PPWR (EU Regulation 2025/40): To the best of our current knowledge and based on information from our raw material suppliers, the products we supply do not contain the heavy metals listed in Article 5, paragraph 4 of the PPWR (lead, cadmium, mercury, and hexavalent chromium) in a total concentration exceeding 100 mg/kg. Pöppelmann neither intentionally adds these regulated substances as components nor are they expected to be present in impermissible concentrations as impurities resulting from the manufacturing process.

Furthermore, according to information from our suppliers, our products do not contain any substances of very high concern (SVHCs as defined in the current REACH Candidate List) in a concentration exceeding 0.1 percent by mass. Pöppelmann does not intentionally add these substances during the manufacturing process. Any presence below this reportable threshold is attributable to unavoidable, raw material-related impurities or technical specifications set by raw material suppliers, which, for us as a processor, represents the technically unavoidable minimum within the context of quality and raw material properties.

Your added values:



Better fit.

Designed for male end connectors in accordance with DIN EN 837-1 and DIN EN 837-3.



Cleaner.

Production in accordance with VDA Band 19 and ISO 16232 in our cleanroom on request.



Better.

Easy-to-grip knurled outer wall for easy removal.



Seals better.

Protection against foreign objects > 1 mm

