

Flange Covers

GPN 650 Type B


Application

The flange covers GPN 650 Type B protect flanges in accordance with DIN EN 1092-1 and DIN 28117 against damage and dirt, seal the opening and protect the sealing face of the flange fitting. The flange covers have additional clamping ribs on the tapered shaft to accommodate larger tolerances.

All information about 100% PCR and the recycling blend can be found at www.poeppelmann.com/en/kapsto/Responsibility.html



www.blauer-engel.de/uz30a



Article	Nominal width mm	A	B	C	H	PCR-PE blue	PCR-PE / PE-LD yellow	PE-LD yellow
						100% PCR	Recycling blend	Virgin material
GPN 650 / 10-R	10	40	7,5	10,5	10	6510010RB61	65100100073	65100100000
GPN 650 / 15-R	15	45	12,5	15,8	10	6510015RB61	65100150073	65100150000
GPN 650 / 20-R	20	59	16	22	15	6510020RB61	65100200073	65100200000
GPN 650 / 25-R	25	68	21	26	15	6510025RB61	65100250073	65100250000
GPN 650 / 32-R	32	78	28	33,5	15	6510032RB61	65100320073	65100320000
GPN 650 / 40-R	40	88	36	41,5	15	6510040RB61	65100400073	65100400000
GPN 650 / 50-R	50	102	46	51	15	6510050RB61	65100500073	65100500000
GPN 650 / 65-R	65	122	60	66	20	6510065RB61	65100650073	65100650000
GPN 650 / 80-R	80	138	74,5	81	20	6510080RB61	65100800073	65100800000
GPN 650 / 100-R	100	162	93	102	20	6510100RB61	65101000073	65101000000
GPN 650 / 125-R	125	205	118	127	20	6510125RB61	65101250073	65101250000
GPN 650 / 150-R	150	245	140	152	20	6510150RB61	65101500073	65101500000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 4 'Materials and application'.

Customer Information pursuant to Art. 16 of the PPWR (EU Regulation 2025/40): To the best of our current knowledge and based on information from our raw material suppliers, the products we supply do not contain the heavy metals listed in Article 5, paragraph 4 of the PPWR (lead, cadmium, mercury, and hexavalent chromium) in a total concentration exceeding 100 mg/kg. Pöppelmann neither intentionally adds these regulated substances as components nor are they expected to be present in impermissible concentrations as impurities resulting from the manufacturing process.

Furthermore, according to information from our suppliers, our products do not contain any substances of very high concern (SVHCs as defined in the current REACH Candidate List) in a concentration exceeding 0.1 percent by mass. Pöppelmann does not intentionally add these substances during the manufacturing process. Any presence below this reportable threshold is attributable to unavoidable, raw material-related impurities or technical specifications set by raw material suppliers, which, for us as a processor, represents the technically unavoidable minimum within the context of quality and raw material properties.

Your added values:



Better fit.

Protection for flanges in accordance with DIN EN 1092-1 and DIN EN 28117.



More versatile.

Design B with additional clamping ribs for accommodating larger tolerances.



Better.

Closes the opening and protects the sealing face of the flange fitting.



Seals better.

Protection against foreign objects >1 mm

