

Flange Covers

GPN 655 Type B



Application

The flange covers GPN 650 Type B protect flanges in accordance with ANSI/ASME B 16.5 against damage and dirt, seal the opening and protect the sealing face of the flange fitting. The flange covers have additional clamping ribs on the tapered shaft to accommodate larger tolerances.

All information about 100% PCR and the recycling blend can be found at www.poeppelmann.com/en/kapsto/Responsibility.html



www.blauer-engel.de/uz30a



PCR-PE blue	PCR-PE / PE-LD yellow	PE-LD yellow
100% PCR	Recycling blend	Virgin material
6550015RB61	65500150073	65500150000
6550025RB61	65500250073	65500250000
6550032RB61	65500320073	65500320000
6550040RB61	65500400073	65500400000
6550050RB61	65500500073	65500500000
6550065RB61	65500650073	65500650000
6550080RB61	65500800073	65500800000
6550100RB61	65501000073	65501000000
6550125RB61	65501250073	65501250000
6550150RB61	65501500073	65501500000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 4 'Materials and application'.

Customer Information pursuant to Art. 16 of the PPWR (EU Regulation 2025/40): To the best of our current knowledge and based on information from our raw material suppliers, the products we supply do not contain the heavy metals listed in Article 5, paragraph 4 of the PPWR (lead, cadmium, mercury, and hexavalent chromium) in a total concentration exceeding 100 mg/kg. Pöppelmann neither intentionally adds these regulated substances as components nor are they expected to be present in impermissible concentrations as impurities resulting from the manufacturing process.

Furthermore, according to information from our suppliers, our products do not contain any substances of very high concern (SVHCs as defined in the current REACH Candidate List) in a concentration exceeding 0.1 percent by mass. Pöppelmann does not intentionally add these substances during the manufacturing process. Any presence below this reportable threshold is attributable to unavoidable, raw material-related impurities or technical specifications set by raw material suppliers, which, for us as a processor, represents the technically unavoidable minimum within the context of quality and raw material properties.

Your added values:



Better fit.

Protection for flanges in accordance with ANSI/ASME B 16.5.



More versatile.

Design B with additional clamping ribs for accommodating larger tolerances.



Better.

Closes the opening and protects the sealing face of the flange fitting.



Seals better.

Protection against foreign objects > 1 mm

