

HV Protection GPN 390 Type A

NEW


Application



www.blauer-engel.de/uz30a

The HV protection GPN 390 Type A is suitable for use in parts and components for hybrid or electric vehicles. It protects connectors, e.g. in the area from the battery to the inverter and electric motor, against corrosion and mechanical damage and offers protection against splash water in accordance with protection class IP44. The cap has gripping edges on the side that allow quick removal and impresses with its functional design as a registered design. The plastic used is made from post-consumer recycled material.

All information about 100% PCR and the recycling blend can be found at www.poeppelmann.com/en/kapsto/Responsibility.html



PCR-PP
turquoise blue
100% PCR

Article	A	F	H	M	
GPN 390 HV 270-2	47	63	8,7	11,1	39005010000
GPN 390 HV STAK 25	58,2	55,1	25	27,7	39006180000
GPN 390 HV STAK 35	85	69	38	10,8	39006130000
GPN 390 HVP 1100	66,7	56,6	9,5	15,1	39006140000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 4 'Materials and application'.

Customer Information pursuant to Art. 16 of the PPWR (EU Regulation 2025/40): To the best of our current knowledge and based on information from our raw material suppliers, the products we supply do not contain the heavy metals listed in Article 5, paragraph 4 of the PPWR (lead, cadmium, mercury, and hexavalent chromium) in a total concentration exceeding 100 mg/kg. Pöppelmann neither intentionally adds these regulated substances as components nor are they expected to be present in impermissible concentrations as impurities resulting from the manufacturing process.

Furthermore, according to information from our suppliers, our products do not contain any substances of very high concern (SVHCs as defined in the current REACH Candidate List) in a concentration exceeding 0.1 percent by mass. Pöppelmann does not intentionally add these substances during the manufacturing process. Any presence below this reportable threshold is attributable to unavoidable, raw material-related impurities or technical specifications set by raw material suppliers, which, for us as a processor, represents the technically unavoidable minimum within the context of quality and raw material properties.

Application Overview

Article	Article number	Manufacturer	Connector family	Housing Type	Number of poles
GPN 390 HV 270-2	39005010000	Rosenberger	HVR	female	2
GPN 390 HV STAK 35-2	39006180000	TE Connectivity	HC-STAK	female	2
GPN 390 HV STAK 35	39006130000	TE Connectivity	HC-STAK	female	2
GPN 390 HVP 1100	39006140000	TE Connectivity	HVA	female	1

Your added values:



More resource-saving.

The plastic used consists of 100 % recycled material.



Better fit.

Protection for High Voltage Connector Systems using our registered design.



Saves time.

Quick disassembly thanks to non-slip grip surfaces.



Cleaner.

Production in accordance with VDA Band 19 and ISO 16232 in our cleanroom on request.



Seals better.

Protection against splashing water from any direction (IPX4) depending on the specific connector design and quality.

[Link to GPN 390 Type A](#)

